

	<b>Quadracep</b>	<b>BiCep</b>	<b>Vertabrae</b>
<b>Physical</b>			
Dimensions (in.)	12Hx12Wx3D	6Hx6Wx.75D	12Hx12Wx3D
Weight (lbs.)	2.75	2	2.95
Cabinet Flex	Concave: 40°; Convex: 25°	Concave: 40°; Convex: 40°	Rigid
Frame Mount	Magnetic	Magnetic	Magnetic
<b>Display</b>			
Pixel Pitch (mm)	3.8 or 2.5	3.8 or 2.5	1.2
Brightness (cd/m2)	Up to 6,500 (dimnable)	Up to 6,500 (dimnable)	Up to 1,000; 1,200; 3,000 or 6,500 (dimnable)
Supported Display Resolutions	Any size/aspect ratio (via processor)	Any size/aspect ratio (via processor)	Any size/aspect ratio (via processor)
Viewing Angle	up to 360°	up to 360°	up to 360°
Grayscale	16-bit/16 scan	16-bit/16 scan	16-bit/16 scan
LED Type	Black or White	Black or White	Black or White
Interactivity (optional)	Infrared or Projected Capacitive	Infrared or Projected Capacitive	Infrared or Projected Capacitive
<b>Connectivity</b>			
Input Ports	Cat6 RJ45	Cat6 RJ45	Cat6 RJ45
<b>Electrical</b>			
Power Consumption	40W per panel	40W per panel	40W per panel
AC Input Power	110 - 220 VAC (60Hz)	110 - 220 VAC (60Hz)	110 - 220 VAC (60Hz)
<b>Environment</b>			
Dust & Water Resistance	IP65 (12.5L/min@30kPa)	IP65 (12.5L/min@30kPa)	IP65 (12.5L/min@30kPa)
Temperture Operation	-20°C (-4°F) to 48°C (118°F)	-20°C (-4°F) to 48°C (118°F)	-20°C (-4°F) to 48°C (118°F)
Humidty Operation	up to 99%	up to 99%	up to 99%